



TRADITIONAL BUILDING SPECIFICATIONS

Concrete

- Footing: 24" wide x 8" deep
- Foundation walls: 8" wide and 9" or 10" wide where there is brick
- Plastic cement and foundation coating sprayed on exterior of foundation wall with Platon or Delta membrane
- Standard poured concrete garage floor: 4" thick
- Brush coating on above grade poured concrete foundation
- Basement floors: 3" thick

Framing

- All working drawings revised by an architect
- House and garage exterior walls are 2" x 6" spruce studs at 16" on centre • Interior walls are 2" x 4" spruce studs at 16" on centre
- Engineered flooring system
- Engineer approved roof truss system at 24" on centre
- Basement frost walls are strapped using construction grade 2" x 4" studs at 24" on centre
- Straight stairwell to basement is framed to receive unfinished drywall on both inside walls, from top of main floor deck down
- 8' ceilings are standard (9' optional)

Exterior doors and windows

- Maintenance free **Energy Star** Vinyl Clad exterior and interior windows (low-e argon) 20 year warranty on thermal pane windows
- Steel insulated door to house from garage
- White finish windows and sliding patio door (as per plan)
- White finish steel insulated front entry door with one sidelight
- Security dead bolt on front door
- Standard of 2 windows 48"x24" in basement
- White insulated Garage Door

Heating

- **HRV** system. Heat Recovery Ventilation connected to furnace duct work • Single natural high efficiency gas furnace with fan
- Sheet metal ducts sized for future air conditioning
- Programmable thermostat
- Dryer vent and bathroom fans venting to exterior
- White interior metal return air grills and plastic diffusers
- Heat on demand water system

Light Fixtures

- "Mushroom" type lighting fixtures.
- 5 pot lights (choice of location)

- Exterior pot lights



TRADITIONAL BUILDING SPECIFICATIONS

Plumbing

- White shower stall & white corner or soaker tub in ensuite bathroom (as per plan) •
White porcelain basins 4" centre.
- White one piece shower-bathtub in main bathroom
- Stainless steel kitchen sink
- ABS draining pipes
- Water supply: Wirsbo

Electrical

- Electrical wall and ceiling switch outlets located as per Ontario Electrical Code, or as per specified blueprint.
- 100 amp service panel in basement (200amp available for a fee)
- All bathrooms on GFCI breaker with one plug per bathroom
- 220-volt outlets for dryer and range
- Four wire bundle from furnace to thermostat (for future air conditioning). •
Rough-in for dishwasher.
- White interior wall switches, plates and plugs (Decora style).
- Smoke detector on every floor as per building code
- CO detector installed as per building code.
- Arc fault breakers as per code
- Standard doorbell chime unit for front door.
- Two exterior weatherproof electrical outlets on GFCI breakers
- Garage comes with two wall plugs and one ceiling light if single garage and two ceiling light if double garage
- Electrical outlet for future garage door opener
- Outlet for on demand water system
- 2 x cable & electrical outlets

Exterior Finish

- Exterior caulking to ensure weatherproof system
- Energy efficient house wrap

Roofing

- Asphalt roof 30 year
- CSA approved roof vents

Siding

- Vinyl siding.

- Aluminum pre-finished soffit and fascia

Masonry

- “Brampton” stone in front of the house

2 | Page
Updated: February 2021



TRADITIONAL BUILDING SPECIFICATIONS

Landscaping

- Sod included (Limoges & Embrun)
- Graded lot
- Tree in the front yard

Deck

- Stairs (and 3x3 landing if applicable) will be provided at the rear exit

Drywall and Insulation

- Exterior walls insulation: R22
- Attic: R60
- Basement insulation: R20
- Walls between garage and house are R22 batt insulation.
- Inside house stairwell leading to basement is framed to receive drywall on both inside/outside walls

Interior Finish Material

- White interior doors will be Colonial Bostonian MDF
- Closet doors: bifolds
- Trim package includes:
 - MDF Baseboard 3-7/8"
 - MDF Crown moulding 4" in kitchen, dining room, living room and hallway - 1/4" round added to the baseboards
 - MDF Casing 2 3/4 " around interior doors and windows

Painting and Staining

- Walls: one coat of primer and two coats of finish (2 colors included)
- Ceiling: white flat finish
- Bathroom ceiling: white semi-gloss latex
- Trims: white finish

Cabinetry

- PVC, Wood & Polyester cabinets in kitchen and bathrooms
- Height of the cabinets will be 7' from the floor (84")
- Crown moulding over cabinet (must be specified on order)

- Countertops are all post-formed Arborite c/w 4" backsplash
- Bank of drawers in kitchen, main bathroom & ensuite (pot drawers extra)

3 | Page
Updated: February 2021



TRADITIONAL BUILDING SPECIFICATIONS

Ceramic Tile

- Ceramic tile flooring in front entrance and bathrooms
- Ceramic tile over soaker or corner tub
- Ceramic tile on walls of 3x5 walk in shower

Closet Shelving

- Closet shelving and rods are maintenance free.
- Linen closet comes with four shelves
- Bedroom closet comes with one rod and one shelf
- Walk-in closets come with a designed rod and shelves

Stairs and Railings

- Two storey homes: carpeted staircase leading to the upper level with a natural oak railing
- Unfinished wood stairs from main floor to basement with a pine handrail •
Unfinished wood stairs from house to garage
 - Cement slab or steps for the front main entrance with a PVC railing (as per plan)

Floor Coverings

- Hardwood floor in living room
- Cushion floor in kitchen, dining room and laundry room
- Carpet in bedrooms, hallways and family rooms
- Ceramic floor in front entrance & all bathrooms

Warranty

TARION:

All homes are protected under the Ontario *New Home Warranty Program*.

Upgrades are available upon client's request.

Note: Les Habitations Leclair Inc. is committed to continual improvement and

refinement of their homes, therefore, these specifications are subject to change without notice.